



RADIUS Series

RADIUS 3"ANSI 150/DN80 PN16/3"NPT INLET

Y35-D24A

2.5"NH MALE OUTLET W/ 12 V STOW LIGHT

\$5908.00 List Price

FEATURES

SPECIFICATIONS

Finish	Stardust Silver
Horizontal Control	Alum Crank Handle
Horizontal Movementdegrees	Continuous 360
Inlet	3.0" ANSI 150
Max Flow	1,500 gpm (6,000 l/min)
Oscillation	No
Outlet	2.5"NH Male
Remote Control	No
Valve Design	No Valve
Vertical Control	Alum Crank Handle
Vertical Movementdegrees	-45 to 90
Weight	37.25

DOCUMENTS

Technical Specifications and Drawings

RADIUS MONITOR EXPLODED PARTS VIEW 3"ANSI 150 X 2.5"NHM (PDF) RADIUS MONITOR EXPLODED PARTS VIEW 4"ANSI 150 X 3.5"NHM (PDF)

Y35-D24A ITEM SPECIFICATION (DOC)

Y35-D24A_45 UP_DEPLOYED - 3D (ZIP)

Y35-D24A_45 UP_STOWED - 3D (ZIP)

 $Instructions\ For\ Installation,\ Safe\ Operation\ and\ Maintenance$

RADIUS MONITOR INSTRUCTION MANUAL (PDF)

Product Brochures

RADIUS MONITOR (PDF)

RADIUS MONITOR - EL MONITOR MONTADO EN PLATFORMA (PDF)

Online Videos

RADIUS MONITOR SERIES VIDEO (MP4)

ABOUT THE RADIUS SERIES

The TFT RADIUS is an easy to install, deck mounted monitor that elevates above the top mounted equipment to get the stream where it counts. The above deck mounting is ideal for apparatus where below deck extension tubes do not fit. The RADIUS elevates by simply pulling the quick release knob and lifting until it's in the locked position. The monitor also includes the ability to flow while in the stowed position.

Learn about RADIUS		