


iVUM (Industrial Valve Under Monitor) Series
IVUM SS 4.0"ANSI X 4.0"ANSI
ZASZ3

EXTERNAL DRAIN/ALSO FITS DN100 PN16

\$2155.00 List Price
FEATURES
SPECIFICATIONS

Drain	No Ball Drain
Finish	American Red
Gear Box Style	Shaft on Side
Inlet	4"ANSI 150
Inlet Flange	Stainless Steel
Operation Energy Source	Manual
Oscillation	No
Outlet	4" ANSI 150
Product	Industrial Valve Under Monitor (IVUM)
Remote Control	No
Valve Design	Stainless
Weight	34.85

DOCUMENTS

Technical Specifications and Drawings

[ZASZ3 ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[INDUSTRIAL VALVE UNDER MONITOR FM APPROVAL \(IVUM\) \(PDF\)](#)
ABOUT THE IVUM (INDUSTRIAL VALVE UNDER MONITOR) SERIES

The 4" Integrated Valve Under Monitor (IVUM) is a robust, low friction loss valve intended for installation directly beneath monitors on a fire protection riser or hydrant stem. The IVUM is built standard with 4" ANSI 150 or DN 100 PN16 flange connections.

All models are equipped with an external automatic drain valve to fully drain the monitor and valve body after use, thus minimizing susceptibility to damage from corrosion and freezing water. An optional internal automatic drain valve located within the half ball allows the standpipe to draw atmospheric air to facilitate draining, even while the half ball is closed. It is beneficial in applications where the standpipe will typically be drained following use, especially where freezing conditions are a concern.

Electrically controlled versions are available.