



Z Series

ZM NOZZLE 2.5" F

ZM141

1250 GPM @ 100 PSI W/FOG TEETH

\$885.00 List Price

FEATURES

Choose your model from the chart on page 107. For example, model ZM131 is 2.5" NH female thread, 1000 gpm at 100 psi nozzle. For assistance in ordering, please call 1-800-348-2686 and speak to a nozzle specialist.

SPECIFICATIONS

Flow Rate	1250 gpm (4800 l/min)
Inlet Coupling Style	Rocker
Inlet Coupling Swivel	Rigid
Outlet Diameter	N/A
Pressure Mode	Single
Type	Fixed
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	7.1
Bumper Material	Metal - aluminum
Certification	FM

DOCUMENTS

Technical Specifications and Drawings

[PARTS LIST: ZM NOZZLE \(PDF\)](#)

[PARTS LIST: ZN NOZZLE \(PDF\)](#)

[PARTS LIST: ZO NOZZLE \(PDF\)](#)

[ZM141 ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SERIES NOZZLES MANUAL \(PDF\)](#)

ABOUT THE Z SERIES

The Z series are fixed gpm water nozzles that are simple and rugged with superior stream quality and reach. The fog angle is user adjustable between 120 degree wide fog and straight stream. The simple and basic design requires no grease or other maintenance. This fixed gallonage fog nozzle family is rated at 100 psi (7 bar) is available with your choice of flow rates:

- ZN: 350, 500, or 750 (1300, 2000, or 3000 l/min)
- ZM: 500, 750, 1000, or 1250 (2000, 3000, 4000, or 4750 l/min)
- ZO: 1250, 1500, 1750, or 2000 (4750, 5500, 6750, or 7500 l/min)