

No image
available

MASTER FOAM Nozzles

MASTER FOAM NOZZLE 2.5" RUSSIAN

ZMF12ARU

500 GPM @ 100 PSI W/10' HOSE

\$1995.00 List Price

FEATURES

SPECIFICATIONS

Flow Rate	500gpm (2000 l/min)
Inlet Coupling Style	Rocker
Inlet Coupling Swivel	Swivel
Kfactor	Kfactor=50
Pattern Actuation Method	Manual w/ Halo
Pressure	100psi (7bar)
Type	Fixed
Weight	0
Detent Swivel	No
Jet Siphon	No
L D H Inlet	No
L D H Outlet	No
Oscillation	No
Package	No
Pistol Grip	No
Pressure Relief Valve	No
Remote Control	No
Safety Shutoff	No
Strainer Float	No
Vertical Oscillation	No

DOCUMENTS

Product Brochures

[Z INDONESIAN MASTERFOAM \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[MASTER FOAM NOZZLE INSTRUCTION MANUAL \(PDF\)](#)

Technical Specifications and Drawings

[LXM-006 \(PDF\)](#)

[MASTER FOAM NOZZLES \(PDF\)](#)

[MASTER FOAM NOZZLES \(PDF\)](#)

[MASTER FOAM SELF EDUCTING NOZZLE \(PDF\)](#)

[ZMF15 FINISHED GOOD PRINT \(PDF\)](#)

ABOUT THE MASTER FOAM NOZZLES

This fixed gallonage fog nozzle is a simple and rugged self-educting foam nozzle with superior stream quality and reach. The fog angle is user adjustable between wide fog and straight stream. The nozzle's baffle is easily removed for flushing debris. Models are rated at 100 psi (7 bar) and are available in two versions.

The smaller version is available in 250, 350, 500 or 750 gpm (950, 1300, 2000, 3000 l/min). The simple flow geometry can educt foam concentrate at .5%, 1%, 3%, or 6%.

The larger version is available with your choice of 1000, 1250, 1500 or 2000 gpm (3800, 4800, 6000 or 8000l/min). The standard swivel coupling is 2.5" NH female threads with customer specific threads available upon request, at no extra charge. The simple flow geometry can educt foam concentrate at 1% or 3%.