

No image available

**MASTER FOAM Nozzles**

**MASTER FOAM ER 3.5”F 12-24VDC**

ZMF17-ER

2000 GPM @ 100 PSI W/10' HOSE

**\$4310.00 List Price**

**FEATURES**

**SPECIFICATIONS**

<b>Flow Rate</b>	2000 gpm (7600 l/min)
<b>Inlet Coupling Style</b>	Rocker
<b>Inlet Coupling Swivel</b>	Full Time Swivel
<b>Kfactor</b>	2000 gpm@100psi -- Kfactor = 200(7600 l/min@7bar)
<b>Pattern Actuation Method</b>	12/24 VDC
<b>Pressure</b>	100 psi (7 bar)
<b>Type</b>	Fixed
<b>Weight</b>	26.25

**DOCUMENTS**

- Product Brochures
- [Z INDONESIAN MASTERFOAM \(PDF\)](#)
- Instructions For Installation, Safe Operation and Maintenance
- [MASTER FOAM NOZZLE INSTRUCTION MANUAL \(PDF\)](#)
- Technical Specifications and Drawings
- [LXM-006 \(PDF\)](#)
- [MASTER FOAM NOZZLES \(PDF\)](#)
- [MASTER FOAM NOZZLES \(PDF\)](#)
- [MASTER FOAM SELF EDUCTING NOZZLE \(PDF\)](#)
- [ZMF15 FINISHED GOOD PRINT \(PDF\)](#)
- [ZMF17-ER ITEM SPECIFICATION \(DOC\)](#)

**ABOUT THE MASTER FOAM NOZZLES**

This fixed gallonage fog nozzle is a simple and rugged self-educting foam nozzle with superior stream quality and reach. The fog angle is user adjustable between wide fog and straight stream. The nozzle's baffle is easily removed for flushing debris. Models are rated at 100 psi (7 bar) and are available in two versions.

The smaller version is available in 250, 350, 500 or 750 gpm (950, 1300, 2000, 3000 l/min). The simple flow geometry can educt foam concentrate at .5%, 1%, 3%, or 6%.

The larger version is available with your choice of 1000, 1250, 1500 or 2000 gpm (3800, 4800, 6000 or 8000l/min). The standard swivel coupling is 2.5” NH female threads with customer specific threads available upon request, at no extra charge. The simple flow geometry can educt foam concentrate at 1% or 3%.